

# **DET NORSKE VERITAS**

### EC TYPE-EXAMINATION CERTIFICATE

Application of: Council Directive 96/98/EC of 20 December 1996 on Marine Equipment as amended by directive 2009/26/EC, issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Directorate. This Certificate is issued by Det Norske Veritas under the authority of the Government of the Kingdom of Norway.

CERTIFICATE NO. MED-B-6338

This is to certify that the Surface materials and floor coverings with low flame-spread characteristics: Adhesives

with type designation(s) Sikaflex®-298

Manufacturer

## Sika Services AG ZURICH, Switzerland

is found to comply with the requirements in the following Regulations/Standards:

Annex A.1, item No. A.1/3.18e and Annex B, Module B in the Directive. SOLAS 74, Reg. II-2/5, II-2/5, II-2/9 & X/3, IMO

MSC/Circ. 1120, 2000 HSC Code 7 and IMO FTP Code

Further details of the equipment and conditions for certification are given overleaf.

Høvik, 2010-09-07 for Det Norske Veritas AS

Notified Body No.: 0575

Eivind Mykland ()
Head of Department

DNV local office: Essen 11.66

This Certificate is valid until

2015-09-07







The Certificate is subject to terms and conditions overleaf. Any significant changes in design or construction of the product, or amendments to the Directive or Standards referenced above may render this Certificate invalid. The product liability rests with the manufacturer or his representative in accordance with Council Directive 96/98/EC, as amended. The Mark of Conformity may only be affixed to the product and a Declaration of Conformity may only be issued when the production/product assessment module referred to in the council directive, is fully complied with.

DET NORSKE VERITAS AS, Veritasveien 1, NO-1322 Høvik, Norway, Tel.: +47 67 57 99 00, Fax: +47 67 57 99 11, Org.No. NO 945 748 931 MVA www.dnv.com Form No.: MED.Ba Issue: April 2010 Page 1 of 2



Certificate No.: MED-B-6338 Item No.: A1/3.18e Job Id.: 344.1-002652-1

#### **Product description**

Sikaflex®-298"

adhesive consisting of 1-component polyurethane.

Amount: 200g/m<sup>2</sup>.

#### Applications/Limitations

Low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Maximum gross calorific value shall be documented separately where applicable, ref. SOLAS Chapter II-2 Reg. 5.3.2.

Each product is to be supplied with its manual for installation and use.

#### Type Examination documentation

Test reporst: No. FX007785 dated 3 June 2010 and FX007771B dated 17 June 2010 from SP Sweden.

Tested according to IMO FTPC Parts 2 and 5.

#### Marking of product

The product or packing is to be marked with name of manufacturer, type designation and Mark of Conformity (see below).

#### **Mark of Conformity**

The manufacturer is allowed to affix the Mark of Conformity according to Article 11 in the Council Directive 96/98/EC on Marine Equipment and shall issue a Declaration of Conformity, only when the module D or E or F of Annex B in the same directive is fully complied with.

Module D: The quality system for production and testing shall be approved by the Notified Body.

Module E: The quality system for inspection and testing shall be approved by the Notified Body.

Module F: Compliance of the products to type as described in this EC Type-Examination Certificate must be verified by

the Notified Body who also shall issue a Certificate of Conformity.



DET NORSKE VERITAS AS, Veritasveien 1, NO-1322 Høvik, Norway, Tel.: +47 67 57 99 00, Fax: +47 67 57 99 11, Org.No. NO 945 748 931 MVA www.dnv.com Form No.: MED.Ba Issue: April 2010 Page 2 of 2